

MB-2 adf

MB-2 adf is the latest model of PR2 plus family, the world's most popular banking teller printer. MB-2 adf is equipped with automatic document feeder, capable to manage multiple documents and cheque processing, all with frontal insertion, frontal or top ejection and sorting when needed. Using integrated scanner, MB-2 adf enables a complete cheque truncation procedure. MB-2 adf manages a wide range of documents, including ID cards, multiple sheets, passbooks and passports. MB-2 adf can read OCR, barcode and MICR, and enable bill payments.

MOST COMPLETE MULTIFUNCTIONAL TELLER SCANNER AND PRINTER

ABLE TO MANAGE ALL KIND OF BANKING MODULES AND PASSBOOKS

HIGH SPEED AUTO ALIGNMENT

INTEGRATED AUTOMATIC DOCUMENT FEEDER

INTEGRATED DOUBLE OUTPUT SORTING TRAYS

CAN BE SHARED BY TWO OPERATORS

HIGHEST PRINTING SPEED, UP TO 560 CPS

(VHSD MODE)

MULTIPLE INTERFACES, INCLUDING LAN WITH

ON-BOARD IMAGE COMPRESSION

EASY TO USE





Multiple interfaces, including LAN and double USB to share machine between two operators



Frontal ADF, excludible, to automatically insert multiple sheets and cheques



Upper sorter to collect printed documents and sort cheques between two trays

TECHNICAL SPECIFICATIONS

Technology	Impact matrix 24 needles		
Resolution	240 x 360 dpi		
Characters per inch	10, 12, 15, 16.6, 17.1 cpi		
Printing speed	VHSD 560 cps	NLQ 185 cps	
(10 cpi)	HSD 510 cps	LQ 125 cps	
	Draft 370 cps	BIM 2000 dps	
Printing width	238,76 mm (94 columns at 10 cpi)		
Line spacing	1/5", 1/6", n/216", n/240"		
Copies	Original + 6 copies		
Interfaces	USB 2.0, USB Hub, RS232C, Parallel IEEE 1284		
	Optional LAN		
Noise	< 54 dBA (ISO 7779 ECMA 132 text)		
ADF	Frontal access up to 50 sheets		
Dimensions (WxDxH)	405 x 415 x 240 mm		
Ribbon Cartridge	10 milions characters		
Document Management	- Paper path: 245 mm wide		
	- Flatbed		
	- Automatic edge recognition & alignment		
	- Automatic thickness adjustment		
	- Excludible Automatic Document Feeder		
	- Two output trays (80+20 sheets)		
	- Software progra	mmable sorting	
Emulations	Olivetti, IBM Proprinter2 & XL24		
Power Consumption	Min. 9W, Max 85W (printing)		
Power Supply	230V / 50Hz, 115V / 60Hz		
Certifications and	CE TuV NRTL		
Security marks	FCC class A verified		
	RoHS		
On board	Image compressio	Image compression, PDF creation	
LAN	IEEE 802.3i/u/x (1	IEEE 802.3i/u/x (10/100 Mbit/s)	
Weight	Around 15 Kg		

MICR		
Туре	Magnetic head + Optical recognition	
Fonts recognized	CMC7, E13B	
SCANNER		
Technology	Contact Image Sensor	
Resolution	600 dpi	
Shades	Colour (24 bit), 256 gray levels, B/W	
Speed	Up to 15 inches/s (grayscale)	
	Up to 8 inches/s (color)	
Acquisition Area	Up to 215 mm wide (A4 / Letter)	
Documents managed	Passbooks, cheques, passports, ID cards, plastic cards, small sheets and A4	
OPTIONS		
Double feed sensor	Ultrasonic	
Touchscreen	4.3 inches, color	
Card reader	ISO 7816 and magnetic (3 tracks)	
UV light	Enable scans of security features	

Performance refers to use of the products in optimal conditions. With the right to change technical characteristics. The registered trademarks are the property of their respective owners.

MB-2 adf is distributed by Olivetti S.p.A.
(10/13) - Code: 29050-02