olivetti

PRT100

THERMAL PRINTER

High-performance printing **speed** and outstanding **autonomy** put **PRT 100** at the top of its product class.

Two-colour printing and outstanding quality mean **sales slips can be personalised** with logos or other graphical elements.

PRT 100 supports a **range of connectivity options** with no need to change printer. Users have no trouble swapping the interchangeable interface modules (RS232, parallel, USB, LAN, etc.).

What's more, **PRT 100 operates in either a to horizontal or a vertical position**. It can also be wall-mounted, depending on the space available and operating requirements.

HIGH PRINTING SPEED AND OPERATING AUTONOMY

2-COLOUR SLIP PRINTING AND PERSONALISATION

EASY PAPER INSERTION AND AUTOMATIC TEAR-OFF

BARCODE READER MANAGEMENT

INTERCHANGEABLE INTERFACE MODULES

HORIZONTAL OR VERTICAL MOUNTING

EXTREMELY simple roll loading

FAST SWITCHING between interfaces: rs232, parallel and usb

HORIZONTAL AND VERTICAL mounting to save counter space

TECHNICAL SPECIFICATIONS

GENERAL

Print technology	Direct thermal
Printing speed	200 mm/s
Resolution	203 dpi x 180 dpi
Printing colors	1 or 2
Printing fonts	10 x 24 / 13 x 27
Characters per inch	56 / 42
Paper width	80 mm
Paper diameter	100 mm maximum
Roll loading	Drop-in
Cutter	Autocutter with partial cut and tear bar
Bar code	UPC-A, UPC-E, JAN8 (EAN8), JAN13 (EAN13), ITF, CODE39, CODE93, CODE128, CODABAR

Interchangeable Interfaces	RS-232 bi-directional parallel, USB, Ethernet
Drawer Interface	Available
User flash memory	384 KB
Power supply	External 24 VDC 110-240 Vac, 50-60 Hz; 72 W
Drivers	Windows 98, 98SE, ME, 2000, XP, OPOS
Emulations	ESC/POS (TM-T88III, TM-T90)
Casing colors	Light grey - Dark grey
Wall mounting kit	Optional
Dimensions (WxDxH)	140 x 217 x 157 mm
Weight	1,9 Kg

CE