





MODULAR

MULTIFUNCTION







d-COLOR MF222^{plus} MF282^{plus} MF362^{plus} MF452^{plus} MF552^{plus}

Already finished..??? That's what users enjoying the benefits of the **new Olivetti colour products** will be asking. All the typical activities of the office workplace will be **smooth, fast and personalisable.** At the same time, thanks to compliance with the **latest environmental impact regulations**, attention will be firmly focused on eco-sustainability.



COLOUR MULTIFUNCTIONAL DIGITAL SYSTEMS

INNOVATIVE CONTROL PANEL WITH MULTI-TOUCH FUNCTIONS REMOTE CONTROL PANEL PRINT QUALITY UP TO 1200 x 1200 DPI WITHOUT LOSS OF SPEED SUPPORT FOR SPECIAL SRA3 AND BANNER PAPER FORMATS PDF/A PRODUCTION WITH OCR SUPPORT DIRECT PRINTING AND SCANNING OF POWERPOINT, EXCEL, WORD DOC 2 GB RAM AND 250 GB HDD SLEEP MODE ENERGY CONSUMPTION FROM 1,2 WATTS

d-COLOR MF222plus MF282plus MF362plus MF452plus MF552plus



9.5" multi-touch control panel with 10-key pad (optional)



Advanced security options, multiple authentication systems

CUTTING-EDGE PERFORMANCE WITH THE FOCUS ON SUSTAINABILITY

With the introduction of the new d-Color MF222plus/ 282plus/362plus/452plus/552plus, Olivetti enhances its A3 colour offer with a complete systems line ranging from 22 to 55 pages per minute and equipped with a series of new features to speed up machine-side activities and make user operations more flexible and fluid, while ensuring security. The systems can be configured in "kiosk" mode, giving access to pre-defined control panel screens where only the functions approved for the specific user account are available. These include **internet** browsing, direct printing and scanning, secure virtuous viewing of the 250 Gb HDD. Special care has also been devoted to the machines' environmental footprint and energy consumption, to offer users significant **cost** savings and ensure eco-sustainability. In compliance with the directives of the new Energy Star 2.0 standard, the new line lowers energy consumption to 1.2/1.4 Watt in sleep mode and has Typical Energy Consumption (TEC) of 1.3/3.5 kWh/week, depending on the product.



CONTROL PANEL OR SMART PHONE?

The new A3 products are equipped with an **ultra-innovative 9" colour control panel** implementing new-generation **multi-touch technology**, to activate a series of functions typical of smart phones, such as a zoom and image rotation. Scrolling of machine functions and related screens is much more fluid thanks to the greater intuitiveness provided by real freedom of movement.

The control panel is the gateway to the machine functions, guiding the user through document **creation/sharing/ archiving procedures.** The high-resolution screen also allows users to consult documents saved in the user box and to display a preview of the current document. Another important innovation is access to the **control panel from a remote tablet or PC**: a replica of the control panel appears on the remote workstation, to provide support or control the system settings.

EXCELLENT FINISHING OPTIONS FOR PRODUCTION OF PROFESSIONAL DOCUMENTS

The advanced print functions of the new Olivetti models offer **fully automatic production of professional documents.** With a choice of 3 finishers, the user always has the ideal solution to turn out high-quality documents (brochures, flyers, presentations, course materials, etc.). Finisher functions can be enhanced with optional modules for **punching**, production of **booklets**, creation of **z-fold leaflets** or **insertion of covers**, as well as offset sorting.

UNLIMITED PRODUCTIVITY


The d-Color MF222plus/282plus/362plus/452plus/552plus are equipped with an internal print controller offering PCL6/PS3 emulation and XPS compatibility, to process the majority of document formats used in today's offices. They also **support Microsoft Office Open XML, to print and save** Microsoft Office docx, xlsx and pptx documents directly to and **from a USB pendrive.** Thanks to the internal web server, documents can also be saved/ printed in cloud mode, **accessing archives resident** for example on a corporate **FTP.** Should PS3 emulation not be sufficient, a **Fiery option with native PS3** is available (not for the d-Color MF222plus) to optimise management of colour profiles and a full range of functions required by graphic artists.



Direct printing and scanning with USB, direct management of Microsoft Office formats



OPTIONS



- * Not available for MF222plus
- ** Also available for MF452plus *** Not compatible when the copier disk is installed **** Also available in an FS-534SD version (integrated SD 511)



d-Color MF452plus




d-Color MF552plus

TECHNICAL CHARACTERISTICS

SYSTEM SPECIFICATIONS	MF222 ^{plus}	MF282 ^{plus}	MF362 ^{plus}	MF452 ^{plus}	MF552 ^{plus}	
Paper-in capacity	Standard: 1.150	Standard: 1.150	Standard: 1.150	Standard: 1.150	Standard: 1.150	
	Max: 3.650	Max: 3.650	Max: 3.650	Max: 6.650	Max: 6.650	
Paper-out capacity	Up to 3.300 cut sheets w	vith finisher, up to 250 cut	sheets without finisher			
Monthly copy/print	80.000 pages	100.000 pages	125.000 pages	150.000 pages	200.000 pages	
throughput						
Black toner duration	Up to 27.000 pages	Up to 27.000 pages	Up to 27.000 pages	Up to 27.500 pages	Up to 27.500 pages	
CMY toner duration	Up to 25.000 pages	Up to 25.000 pages	Up to 25.000 pages	Up to 26.000 pages	Up to 26.000 pages	
Duration black images unit	Up to 70.000 pages	Up to 120.000 pages	Up to 120.000 pages	Up to 130.000 pagine	Up to 135.000 pages	
	(Drum)	(Drum)	(Drum)	(Drum)	(Drum)	
	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	
Denotion CDDV in a new it	(Developer)	(Developer)	(Developer)	(Developer)	(Developer)	
Duration CMY images unit	Up to 55.000 pages	Up to 75.000 pages	Up to 90.000 pages	Up to 95.000 pages	Up to 95.000 pages	
	(Drum)	(Drum)	(Drum)	(Drum)	(Drum)	
	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	
Custom dimensions (AALDed)	(Developer)	(Developer)	(Developer)	(Developer)	(Developer)	
System dimensions (WxDxH)	615 x 685 x 779 mm	615 x 685 x 779 mm	615 x 685 x 779 mm	615 x 685 x 921 mm	650 x 685 x 921 mm	
Weight Automatic duplex	Approximately 85 kg A5-SRA3, 52-256 gm ²	Approximately 85 kg	Approximately 85 kg	Approximately 101 kg	Approximately 101 kg	
System memory	2.048 Mb					
Hard disk	250 Gb					
Interface		1.000-Base-T Ethernet, US	ER 2.0			
Network protocol			therTalk), SMB, LPD, IPP, SN	ІМР НТТР		
Paper format				11111		
Paper weight	A6-SRA3, personalised paper format, banner paper max. 1.200 x 297 mm 52-300 gm ²					
Power absorption/	220-240V / 50/60 Hz Ma	15 kW (system)				
consumption	220-2401 / 50/00 112 1012	IX 1.5 KW (System)				
consumption						
PRINTER						
PRINTER Print resolution	1.800 equivalent x 600 d	lpi, 1.200 x 1.200 dpi				
	1.800 equivalent x 600 d 800 Mhz	lpi, 1.200 x 1.200 dpi				
Print resolution CPU Type controller Page description	800 Mhz	lpi, 1.200 x 1.200 dpi PostScript 3 (CPSI 3016), XI	PS			
Print resolution CPU Type controller Page description language	800 Mhz PCL 6c (XL3.0), PCL 5c, F	PostScript 3 (CPSI 3016), XI				
Print resolution CPU Type controller Page description	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bir	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se	PS rver 2003/2008 32/64bit, 2	2008 R2/2012 64bit,		
Print resolution CPU Type controller Page description language Operating system	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix		2008 R2/2012 64bit,		
Print resolution CPU Type controller Page description language Operating system Print fonts	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin	rver 2003/2008 32/64bit, 2	· · · · · · · · · · · · · · · · · · ·		
Print resolution CPU Type controller Page description language Operating system	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and	· · · · · · · · · · · · · · · · · · ·	(LSX, PPTX)	
Print resolution CPU Type controller Page description language Operating system Print fonts	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and	· · · · · · · · · · · · · · · · · · ·	(LSX, PPTX)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and	· · · · · · · · · · · · · · · · · · ·	(LSX, PPTX)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning,	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection	· · · · · · · · · · · · · · · · · · ·	(LSX, PPTX)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm	· · · · · · · · · · · · · · · · · · ·	(LSX, PPTX)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour)	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional)	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional)	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional)	· · · · · · · · · · · · · · · · · · ·	(LSX, PPTX)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi)	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals	Mixplex, OOXML (DOCX, X	-	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm	Mixplex, OOXML (DOCX, X	- Up to 80 opm/160 ipm	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour)	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post: Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard)	- Up to 80 opm/160 ipm (standard)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi)	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm	Mixplex, OOXML (DOCX, X	- Up to 80 opm/160 ipm	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post: Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard)	- Up to 80 opm/160 ipm (standard)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post: Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard)	- Up to 80 opm/160 ipm (standard)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard)	- Up to 80 opm/160 ipm (standard)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic feeds	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post: Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF A6-A3, 35-163 gm ²	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard)	- Up to 80 opm/160 ipm (standard)	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic feeds Scan resoluti	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bir Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post: Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF A6-A3, 35-163 gm ² Max.: 600 x 600	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard) 100 originals	- Up to 80 opm/160 ipm (standard) 100 originals	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic feeds	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bir Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF A6-A3, 35-163 gm ² Max.: 600 x 600 Network TWAIN scan, sc	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional)	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard) 100 originals	- Up to 80 opm/160 ipm (standard) 100 originals	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic feeds Scan resoluti Scan modes	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post: Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF A6-A3, 35-163 gm ² Max.: 600 x 600 Network TWAIN scan, sc scan-to-WebDAV, scan-t	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals scan-to-FTP, Scan-to-SMB	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard) 100 originals (scan-to-Home), scan-to-Ba	- Up to 80 opm/160 ipm (standard) 100 originals ox,	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic feeds Scan resoluti	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF A6-A3, 35-163 gm ² Max.: 600 x 600 Network TWAIN scan, sc scan-to-WebDAV, scan-t	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals scan-to-FTP, Scan-to-SMB PDF, encrypted PDF, sercha	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard) 100 originals (scan-to-Home), scan-to-Ba	- Up to 80 opm/160 ipm (standard) 100 originals ox,	
Print resolution CPU Type controller Page description language Operating system Print fonts Print functions SCANNER Scan speed (B/W and colour) R-ADF (300 dpi) Scan speed (B/W and colour) Dual scan (300 dpi) Automatic document feed Paper weight automatic feeds Scan resoluti Scan modes	800 Mhz PCL 6c (XL3.0), PCL 5c, F Windows VISTA 32/64bi Macintosh OS X 10.x, Un 80x PCL Latin, 137x Post Direct printing PCL, PS, T "Easy Set" job planning, Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals R-ADF o Dualscan ADF A6-A3, 35-163 gm ² Max.: 600 x 600 Network TWAIN scan, sc scan-to-WebDAV, scan-t	PostScript 3 (CPSI 3016), XI t, Windows 7 32/64bit, Se ix/Linux/Citrix Script 3, Emulation Latin IFF, XPS, PDF and encrypte superimposition, waterma Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals	rver 2003/2008 32/64bit, 2 ed PDF files, Mixmedia and rk, copy protection Up to 80 opm (optional) 100 originals Up to 80 opm/160 ipm (optional) 100 originals scan-to-FTP, Scan-to-SMB PDF, encrypted PDF, sercha	Mixplex, OOXML (DOCX, X - Up to 80 opm/160 ipm (standard) 100 originals (scan-to-Home), scan-to-Ba	- Up to 80 opm/160 ipn (standard) 100 originals ox,	

FINISHER OPTIONS



COPIER	MF222 ^{plus}	MF282 ^{plus}	MF362 ^{plus}	MF452 ^{plus}	MF552 ^{plus}		
Copy/print speed	22	28	36	45	55		
A4 (B/W and colour)							
Copy/print speed	14	14	18	22	27		
A3 (B/W and colour)							
Duplex speed	22	28	36	45	55		
A4 (B/W and colour)							
First copy/print out	6,9	5,9	5,3	4,6	4,1		
(B/W)							
TFirst copy/print out	8,3	7,7	6,9	5,5	4,6		
(colour)							
Warm-up time	Approximately 20*	Approximately 20*	Approximately 20*	Approximately 20*	Approximately 20*		
	* (warm-up time may vary c	* (warm-up time may vary depending on type of use)					
Print process	Electrostatic, indirect Tandem laser copy						
Toner type	Chemical polymer tone	Chemical polymer toner					
Copy resolution	600 x 600	600 x 600					
Gradations	256 gradations	256 gradations					
Original format	A5-A3						
Enlargement	25-400 %, with 0,1 %	25-400 %, with 0,1 % increments, automatic zoom					
Copy functions	Chapter, insertion page and cover, trial copy (print and display), adjustment trial print, digital creative functions,						
	job memory, poster me	job memory, poster mode, image repeat, superimposition, watermark, stamp, copy protection, badge copy					
USER BOX SPECIFICATION	ON						
Max. box memory	Up to 3.000 document	Up to 3.000 documents or 10.000 pages					
Types of user box	Public, private (with password or authentication), group (with authentication)						
Types of system box	Secure printing, encrypted PDF printing, fax receipt, fax polling						
B ()							

Types of system box	in box secure printing, encrypted i bi printing, tax receipt, tax polinig			
Box functions	Re-print, combination, download, send (e-mail, FTP, SMB and fax), box-to-box copy			
FAX				
Fax standard	Super G3 (optional)			
Fax trasmission	Analog, i-Fax, colour i-Fax (RFC3949-C), IP-Fax			
Fax resolution	Max. 600 x 600 (ultra-fine)			
Fax compression	MH, MR, MMR, JBIG			
Modem Fax	Up to 33,6			
Fax output	2.100 (single + group)			
Fax functions	Polling, deferred transmission, PC-Fax, reception in private boxes, reception via email/FTP/SMB, up to 400 job programs			

Performance refers to use of the product in optimal conditions. With the right to change technical characteristics. The registered trademarks are the property of their respective owners. The d-Color MF222plus/MF282plus/MF362plus/MF452plus/MF552plus are distributed by Olivetti S.p.A. (08/14) - Code: 29020-03-w

OLIVETTI S.P.A. VIA JERVIS 77 10015 IVREA (TO) ITALY www.olivetti.com

